Validation of UARS MLS 183 GHz H₂O Measurements

W.A. Lah oz 4MR. Suttie¹, J. Froidevaux², R.S. Harwood¹, C.L. Lau³
T. A. Lungu², G.E. Peckham³, H.C. Pumphrey¹, W.G. Read²
Z. Shippony², 1{. A. Suttie³, J.W. Waters², G. E. Nedoluha⁵
S.J. Oltmans⁶, J.M. Russell 111, W. A. Traub⁸

- ¹ Edinburgh University, Edinburgh, Scotland, UK.
- ² Jet Propulsion Laboratory, Pasadena, CA, USA.
- ³ Heriot-Watt University, Edinburgh, Scot land, UK.
- ⁴ CG AM, Reading University, Reading, England, UK.
- ⁵ Naval Research Laboratory, Washington, DC, USA.
 - ⁶ NOAA CMDL, Boulder, CO, USA.
- ⁷ NASA Langley Research Centre, Hampton, VA, USA
- 8 Harvard-Smithsonian Centre for Astrophysics, Cambridge, M A, USA.

2nd March 1995

Abstract. The Upper Atmosphere Research Satellite (UARS) Microwave Limb Sounder (MLS) makes measurements of thermal emission at 183.3 GHz which are used to infer the concentration of water vapour over a pressure range of 46 hPa to 0.2 hPa (~ 20 km to ~ 60 km). We provide a validation of MLS H₂O by analysing the integrity of the measurements, by providing an error characterization and by comparison with data from other instruments. It is estimated that Version 3 MLS H₂O retrievals are accurate to within 20-25% in the lower stratosphere and to within 8-13% in the upper stratosphere and lower mesosphere.

The precision of a single profile is estimated to be $\sim 0.15\,\mathrm{ppmv}$ in the mid-stratosphere and $0.2\,\mathrm{p}$ pmv in the lower and upper stratosphere. in the lower mesosphere the estimate of single profile precision is 0.25– $0.45\,\mathrm{ppmv}$. During polar winter conditions $\mathrm{H}_2\mathrm{O}$ retrievals at $46\,\mathrm{hPa}\,\mathrm{can}\,\mathrm{have}$ a substantial contribution from climatology. The vertical resolution of MLS $\mathrm{H}_2\mathrm{O}$ retrievals is $\sim 5\,\mathrm{km}$.

1. Introduction

The Upper Atmosphere Research Satellite (UARS) was launched 011 12 September 1991 carrying a payload to measure the chemistry, dynamics and energy balance of the middle atmosphere [Reber, 1990]. This paper concerns the data validation of middle atmosphere distributions of H₂O as measured by the Microwave Limb Sounder (MLS) [Barath et al., 1993; Waters, 1993].

The MLS instrument is a joint USA-UK experiment employing a three radiometer design, with a 183 GHz radiometer built in the UK that measures H₂O using the emission from the 183.3 GHz H₂O line and O₃ using the emission of the 184.4 GHz O₃ line. For details of the spectroscopy of these two lines see Waters [1976, 1993]. This paper discusses the MLS H₂O measurements and their validation, concentrating on the Version 3 MLS data files, the first version to be made publicly available. Companion papers describe the calibration of the MLS instrument [Jarr 104 et al., 1994], the 'forward model' [Read et al., paper in preparation], and validation of MLS ClO [Waters et al., 1994], O₃ [Froidevaux et al., 1994] and temperature and tangent-point pressure [Fishbein et al., 1994]. Froidevaux et al. [1994] give a description of the general algorithms used for retrieving parameters from the calibrated MLS radiances.

In the following sections we provide validation of MLS 11,0 data by discussing data

' ressing and the integrity of th e radiances used in the retrieval process, by performing an error analysis and by making comparisons between MLS H₂O and other measurements. On the basis of these studies we provide estimates of the accuracy and precision of MLS H₂O data. We also discuss outstanding issues and further work associated with this dataset.

2. MLS Version 3 Data Processing

The output of the 183 Gllz radiometer is down-converted through an Intermediate Frequency (IF) stage into a 15 channel, 500" Mllz wide filter-l)al]k, centred on the 183.3 Gllz line. The measured radiances include the contributions of a primary sideband and an image sideband [Jarnot et al., 1994]. From the intensity and spectral characteristics of this emission and its variation as the MLS field of view (FOV) is scanned vertically across the atmospheric limb, profiles of ll₂O are inferred. The width of the MLS FOV half-power points is 3.7 km in the vertical and 7.2 km in the horizontal. The horizontal resolution along the line of sight (perpendicular to the UARS velocity vector) is ~ 400 km, set by the physics of radiative transfer.

The measurement latitudinal coverage is from 340 on one side of the equator to 80° on the other. UARS yaws around at ~ 36 day intervals (a 'UARS month'), when MLS high latitude coverage switches from one hemisphere to the other. Within each UARS month, the UARS orbit precesses slowly with respect to local solar time, so that tile measurements sweep through all local solar times during a UARS month, coming ~ 20 minutes earlier each day at a fixed latitude.

The UARS project has defined four levels of data (Level 0 → Level 3) which represent the data flow fl'oil) raw telemetry data, Level o, to fields of geophysical parameters on

standard grids, Levels 3AT, 3AL and 3B. UARSLevel 1 data consist of calibrated radiances for each channel, their measurement precisions, and related instrument data. The MLS radiance values are expressed as brightness temperatures in units of degrees Kelvin and have a random uncertainty associated with them. UARS Level 2 data consist of geophysical parameters, and numerous diagnostics. The UARS Level 2 data are on a grid chosen by each instrument team. MLS Level 2 data consist of vertical profiles (the vertical coordinate being $-\log_{10}(p)$, p being pressure in hPa) of geophysical parameters which have a spatial and temporal location associated with them. The retrieval algorithm used to derive L evel 2 data is based on a combination of a priori and measurement information [Rodgers, 1976; Froidevaux et al., 1994] and makes use of the forward model, developed by Read et al. [paper in preparation, to calculate the influence functions (also known as weighting functions). It is clear that the integrity of the Level 2 and Level 3 data is very dependent on the integrity of the Level 1 radiances and considerable effort has been expended in assessing the robustness of these radiances [inter alia Jarnot et al., 1994]. More details will be provided in section § 3 1)('10W.

UARS Level 3AT data are geophysical parameters gridded each 65, 536 s time interval onto pressure Sill'fam p_n , where $p_n = 1000 \times 10^{-n/6} \,\mathrm{hPa}\,(\mathrm{n} = \mathrm{O}, \ldots, 42)$ (which would correspond to a constant height spacing of 2.7km in an isothermal atmosphere with a constant pressure scale-height of 7km). Each day contains 1318 or 1319 profiles. The MLS Level 3AT retrieved water vapour volume mixing ratio profile is represented as a piecewise-linear function with breakpoints at alternate, even numbered, UARS pressure surfaces, e.g. at 10, 4.6, 2.2 and 1 hPa. (The M 1,S Level 2 retrieved profiles are similarly represented.) The water vapour mixing ratios on the even-numbered surfaces are the retrieved breakpoint

in the mixing ratios on adjacent even-numbered surfaces. C.g. 6.8, 3.2 and 1.5 hPa, are averages of the mixing ratios on adjacent even-numbered surfaces. This means that the vertical resolution of Level 3AT H₂O profiles imposed by this representation corresponds to a height resolution of ~5.4 km, Level 3AJ, data are like 3AT data except gridded every 4° in latitude and temporal information is lost. There are generally only about 2/3 the number of Level 3AT profiles in a Level 3AL file, namely close to 840 profiles. The Level 3B data comprise globally mapped representations of 3AJ, data.

Retrievals of MLS data are constrained with a priori information, with the result that, where there is poor information content in the ML S measurements, the retrieved values and their associated uncertainties relax to the a priori values. Consequently, it is important for the retrieval algorithm to have reasonable a priori inputs (values and error information) so that they do not over-constrain or under-constrain the solution,

In the case of MLS, the a priori inputs (or 'climatology') are based 011 a month-dependent climatology developed by the UARS science team [infer alia MA 1' Handbook 31,1989]. The UARS H₂O climatology [Remsberg et al., 1990] consists mainly of monthly zonal means from the Limb Infrared Monitor of the Stratosphere (LIMS) [Russell et al., 1984] for sevenmenths (November M ay), 100 alia to 1.5 hPa and 56°S to 84°N. From 1.5 hPa to 0.5 hPa, radiance averaged profiles from 1. MS data are used. Besides the LIMS data, ground-based microwave data [see, for example, Bevilacqua et al., 1985, 1987; Tsou et d., 1988] are used in the mesosphere for pressures of 0.5 III)a to 0.01 III'ii. The 11₂0 UARS climatology was extended to the whole of the year by assuming hemispheric symmetry in the seasons. Extensions where UARS climatology is unavailable make use of default values which were constructed from the Caltech/JPL photochemical model for a 1nid-latitude equinox day. A diagonal a

priori error covariance matrix is used. In the stratosphere the assumed a priori—uncertainty is set to 2 pp mv. By comparison, the standard deviation about the zonal mean of typical LIMS H₂O profiles for May and October tends to be less than 1 ppmv throughout most—of the stratosphere [Remsberg et al., 1990]. This strongly suggests—that an a priori error—of 2 ppm v for MLS H₂O retrievals—ill—the stratosphere is large and is unlikely to overconstrain the solution to the input climatology. Tests with significantly larger a priori errors gave results which were negligibly different from the standard retrievals within the useful—vertical range of the data.

The uncertainty, σ , associated with each retrieved 11,0 profile is computed by the retrieval algorithm and is stored along with the retrieved value in the Level 2 and Level 3 files as a quality indicater. This uncertainty, which includes contributions from random noise and from certain systematic errors, is obtained by propagating the precisions of the radiance measurements (a Level 1 product), the estimates of uncertainties in the constrained parameters and the estimates of inaccuracies in the forward model through the retrieval software.

A more detailed discussion]] of the errors associated with Version 3 MLSH₂O retrievals is presented in sections § 3 and 4.

At the conclusion of the retrieval, the ratio of the estimated uncertainty to its a priori counterpart is formal. This ratio is sometimes termed the 'error ratio'. When this ratio exceeds 0.5 (i.e. the retrieved mixing ratio has a contribution from the climatology which exceeds 25%) the quality is set negative to flag the dependence of the retrieval on the climatology. Typically, for every profile, this tends to occur at or above the ().()46 rPa retrim'al level and below 46 hPa. However, at high latitudes in winter, the ratio can exceed ().5 at 46 hPa and at 22 hPa (see section § 6).

An important feature of the UARS MLS experiment is that it measures O_3 at two different frequencies (1 84.4 GHz and 206.1 GHz) using two different radiometers (183 GHz and 2 0.5 GHz). In regions of the atmosphere where both measurements are sensitive to changes in constituent amount, the availability of two independent O_3 measurements means that intra-MLS comparisons can be carried out and, for example, the consistency of the calibration of the 183 GHz and 205 GHz radiometers can be CHc.eked. The Version 3 algorithms contain an adjustment to the pointing angle of the 183 GHz radiometer field of view (FOV), based on a comparison between the two ozone retrievals and in-flight calibration involving scans across the disk of the moon [Froidevaux et al., 1994]. This has had an impact on the MLS Π_2O distribution, namely a reduction of $\sim 5\%$ in retrieved stratospheric values by comparison with Version 2 retrievals.

The MLS radiances can contain an offset, or baseline, which is caused by a variety of effects such as insufficiently accurate modelling of the sidelobes of the antenna FOV. It does not depend on frequency, but Call change from one tangent height to the next. The baseline is handled by retrieving it along with the water vapour. The a priori value of the baseline is taken to be the retrieved value for the tangent height above the one being retrieved. The a priori uncertainty for the baseline is 3 K. Above 40 km, where there should be 1 little or no signal in the wing channels, the baseline can be retrieved very accurately. It usually has a value Of about 2 K at 80 km dropping to 1.51< at 401{111. In the lower stratosphere, it becomes difficult to distinguish between baseline effects and radiation which is due to water vapour. The retrieved baseline often increases sharply to between 4 K and 8 K in this region. This may be a source of systematic error in the water vapour retrim'al in the lower stratosphere and is a subject of current investigation.

The Version 3 retrieval algorithm assumes linearity. Accordingly, it is less accurate in regions where the atmosphere is optically thick and the radiative transfer equations are correspondingly non-linear. The 183.3 GHz H₂O emission line measured by MLS is relatively strong and, consequently, tends to have high opacities throughout the stratosphere: the line centre becomes optically thick for levels in and below the upper stratosphere; the wings of this line become optically thick for levels in and below the lower stratosphere. Furthermore, no tropospheric retrievals of H₂O are possible with the 183 GHz radiometer due to limited bandwidth. To prevent the retrieval algorithm from operating in regimes that are non-linear, an 'opacity criterion' [Froidevaux et al., 1994] has been devised to discard measurement information when the estimated optical depth exceeds a value of 1.0.

Investigations on the data quality of Version 3 MLS H₂O provide strong evidence that retrievals at the 46 hPa level at high latitudes in winter can have a substantial contribution from the *a priori* input. Detailed studies indicate that this is due to a combination of the atmosphere being optically thick and the very low temperatures prevailing in these regions (especially in winter), which results in estimated opacities for these cases exceeding the 'opacity criterion' and a consequent loss of information content. In these circumstances most of the information is contributed from fields of view with tangent pressures less than 46 hPa.

3. Signals and C losure

In this section we discuss the integrity of the radiances measured by band 5 of the MLS 183 GHz radiometer. We present a test of consistency and investigate the extent of closure of these radiances. We also discuss closure issues for the retrieved H₂O mixing ratios by

means of simulated retrievals.

3.1 Radiances

An important aspect of validating the MLS II₂O retrievals is the examination of the radiances measured by the instrument. Figure 1 shows calculated limb emission in the spectral region 182-187 GHz which includes both spectral sidebands of band 5 and band 6 (MLS band 6 radiances are used for retrieving O₃, see Froidevaux et al., 1994). The position of the local oscillator (LO) at 184.78 GHz is indicated on the plot. Spectra are shown for tangent pressures in both the upper and lower stratosphere. Spectral lines of all molecules which are thought to be important are included in the calculation employing spectral data from the JPL catalogue [Pickett et al., 1992]. The primary (signal) sideband is dominated by the 183.3 GHz H₂O line whereas the image sideband contains no strong lines, giving a 'clean' measurement of 183 GHz H₂O limb emission. There are 15 spectral channels spanning the 510 MHz bandwidth of band 5. For each channel the sideband ratio, describing the relative response of the primary and image sidebands, has been measured. Details of the bandwidth and frequencies of the channels, of the vertical scan patterns and of the procedures for converting the Level 0 data to calibrated radiances and error estimates (Level 1 data) are given in Jarnot et d., [1994]. On 31 st October 1991, the vertical resolution of the scan pattern was increased in the lower stratosphere to improve measurements in this region.

Typical examples of measured radiances in band 5 are shown in Figures 2 and 3. Vertical profiles of the radiances in channels 1 to 8 are plotted in Figure 2. Channel 8 measures the limb emission at the line centre and saturates in the primary sideband at tangent heights of $\sim 50 \, \mathrm{km}$. Between $\sim 50 \, \mathrm{km}$ and $\sim 20 \, \mathrm{km}$, where the primary sideband of channel 8 is

saturated and there is no significant signal in the image sideband, variations in that radiance reflect variations in the temperature of the atmosphere. For channel 1, on the wing of the 183.3 GHz line, the signal in the primary sideband is not significant until the FOV is scanned down to tangent heights of $\sim 30\,\mathrm{km}$. The signal in the image sideband begins to make a significant contribution in all channels at $\sim 20\,\mathrm{km}$. The three panels in Figure 3 display typical measured spectra in the mesosphere, 11])])('1" stratosphere and lower stratosphere. The width of each channel is depicted by a horizontal bar and the 1σ measurement uncertainty is represented by a vertical bar. The effect of pressure broadening is clearly seen as the tangent pressure increases.

3.2 Internal Consistency

In an isothermal atmosphere, when a spectral channel is saturated, the radiance in that channel should represent the black-body emission for the temperature of the atmosphere and is insensitive to the amount of atmospheric constituent. One test of consistency of the measured radiances is to compare them with the retrieved temperatures for a profile which is nearly isothermal. Figure 4 shows the radiances for such a profile, with the temperature also plotted and scaled by the sideband ratio. The radiances behave qualitatively as expected; all channels appearing to saturate within 10 K of a brightness temperature of approximately 1251<. The center channels saturate at a slightly higher temperature because the profile is not quite isothermal; the temperature increases slightly with height. The saturation is less clear in the wing channels because the image sideband starts to receive radiation at tangent heights where the principal sideband is not saturated.

It is clear, however, that the measured radiances tend to saturate at a brightness tem-

Approximately 1 K Of this discrepancy is due to a systematic bias in the MLS temperature retrieval (see Fish bein et al., 1994); another 2 K is the baseline. The rest is possibly due to inexact knowledge of the sideband ratios. The effect this would have on the Version 3 retrieval is small, because radiances close to saturation are not used, while those far from saturation are not toosensitive to sideband ratio. 110WCVCV, it is necessary that we resolve this discrepancy before a full nonlinear retrieval can be carried out.

3.3 Closure in Radiances

Another test of a retrieval scheme is the extent to which radiances calculated from the retrieved product agree with the measured radiances within the expected noise. Discrepancies larger than instrument noise indicate a lack of adequate fit to the measured radiances and indicate some type of systematic error. The source of this error could either be in the retrieved product or in the forward model which calculated the radiances. We define the radiance residual as the measured radiance minus the calculated radiance, and the nature of the variation of these residuals with respect to height, spectral channel and location is discussed.

The plots in Figure 5 show typical variations of radiance residual with height, for each of the 15 channels of band 5, for an equatorial location on 10th January 1992. The horizontal bars represent the 1σ measurement noise. The plots in Figure 5 relate to a single profile, but they are representative of the generally observed variation of radiance residual with height. Figures 6 and 7 show plots of average residuals within latitude bands 10°N-10°S and 60°N-80°N, respectively, for 10th January 1992. Each of these figures displays the variation of

the average residuals within eight selected pressure bins ranging from 100 hPa to 0.01 hPa. Vertical bars represent the standard error on the mean measured radiance for a particular channel within a particular pressure range and latitude band. In general, this quantity is small and due to the vertical scale of the plots in Figures 6 and 7 these vertical bars are visible in the pressure range 0.032-0.01 hPa only. The number of limb views which were included in each of the calculations of the average residual ranges from around 200 for the pressure range 0.032-0.01 hPa to about 800 for the pressure range 100-31.6 hPa. Within the two latitude bands mentioned above, similar variations of average residual with spectral channel are found, except for channels 7 and 8 in the mesosphere.

The main features of the residuals in Figures 5-7, are as follows. A large negative residual of $\sim -15\,\mathrm{K}$ (10-15%) appears in all channels at around 15 km (see Figure 5). At this level in the atmosphere, the Version 3 MLS $\mathrm{H_2O}$ retrievals provide essentially no measurement information and a priori abundances are climatological. If the a priori $\mathrm{H_2O}$ amount is an overestimate of the truth at around 15 km, then the recalculated radiances will be greater than the measured radiance which would result in a negative residual. This occurs below the lower limit of the useful vertical range for MLS Version 3 $\mathrm{H_2O}$ retrievals (see Section §4).

Referring to Figures 6 and 7, certain systematic patterns are evident in the spectral signature of the residuals. In the lower stratosphere there appears to be an asymmetry in the residuals for the wing channels. In the pressure range 31.6-10 hPa channels 13, 14 and 15 exhibit negative residuals whereas the residuals in channels 1, 2 and 3 are positive. Channels 4-11 have positive residuals of between 2-4 K (1-4%) in the latitude bin 10°N-10°S and smaller positive residuals of 1-2 K (~ 1%) in the latitude bin 60°N-80°N. These residuals

patterns may be the result of a combination of errors in parameters such as the antenna transmission or the relative response of the primary and image sidebands. In the upper stratosphere and lower mesosphere (panels for)) (*ssiii* (*ranges 10- 3.16 hPa, 3.16 l hPa and 1- 0.32hPa) there appears to be an oscillatory behaviour of the residuals across the band. This signal may be related to errors in the assumed line shape and is under investigation. In the pressure range 0.32- 0.1 hPa the residual pattern differs between the latitude bins 10°N-10°S and 60°N-80°N. For this pressure range, channel 9 exhibits a large positive residual in both latitude bins, however, channels 7 and 8 switch from having positive residuals in the range 10° - 10°S to having negative residuals in the 60°N-80°N range. Residuals for ascending and descending parts of orbits were 100ked at separately to check whether this effect was due to a Doppler shift caused by winds which are not modelled. However, there was no significant difference in the patterns of residuals between ascending and descending sides of the orbits.

This section has described the main systematic features which occur in the residuals for MLS Version 3 H₂O retrievals. The possible sources of these features, including—errors antenna transmission, assumed line shape, sideband ratios, and the alignment Of the field of view are being investigated.

in

3.4 Closure of retrievals

We now investigate the extent of closure of the MLS Version 3 H₂O retrievals in order to estimate the magnitude of 'numerical errors' arising from the software used to create the Version 3 data files. This involves performing a retrieval using simulated radiances which are calculated from an assumed H₂O distribution. The retrieved H₂O field is then compared with the original (true) field. In this work, we have employed a smoothed version of the $\rm H_2O$ distribution as retrieved by MLS for 17tH September 1992 as the true distribution. Simulated radiances were produced based on this field and these radiances, with simulated noise added, were then used as input to the retrieval. We do not expect perfect closure as the retrieval is based on assumptions of linearity and does not fully utilise the set of radiance measurements when the atmosphere is deemed to be optically thick. This is particularly important for limb views with tangent heights in the lower stratosphere.

The zonal mean of the smoothed H₂O field employed as the true distribution and the zonal mean of the retrieved H₂O field are displayed in panels (a) and (b) of Figure 8, respectively. The zonal mean difference between these two fields is plotted in panel (c) of Figure 8, and the root-mean-square (rms) difference is shown in panel (d). The vertical range of the plots has been limited from 46 hPa to 0.2 h Pa. Below 46111'a the retrieved values are climatological and above 0.2 hPa there exist known problems with the retrieval (see section§ 6).

The rms difference between the true and the retrieved $\rm H_2O$ distributions is approximately 0.2 ppmv (2-5%) throughout tile stratosphere with the retrieval having the tendency to overestimate the true distribution in the lower stratosphere. At latitudes greater than 600 (in either hemisphere), on the 46 hPa retrieval surface the rms difference can be larger than 0.6 ppmv (~ 15 %). This is caused by a 10ss of measurement information due to estimates of large optical thickness in these regions, and this results in the retrieved values having a substantial contribution from the *a priori*. Above 1 hPa the zonal mean difference remains at ~ 0.2 ppmv (~ 4 %), but the rms difference increases from ~ 0.3 ppmv (~ 5 %) at 1 hPa to nearly 1 ppmv (~ 12 %) at 0.2 hPa. This is due mainly to an increase in random errors,

such as radiance noise and uncertainty in the retrieved temperature, and to an increase in the step size of the FOV scan.

In general, the closure of the retrievals is satisfactory throughout the stratosphere, and the above mentioned features are subjects of current investigation (see section §6). The error analysis presented in section §4 takes account of numerical errors produced by the retrieval process.

4. Estimated Uncertainties

In this section we present the estimated uncertainties for the Version 3 MLS H₂O retrievals from band 5 of the 183 GHz radiometer. The estimated uncertainties are based on everything known apart from comparisons with other data sets (see section § 5). We also include information on the averaging kernels (defined below) and vertical resolution of the retrievals. Firstly, a brief review of the method of error characterization is given. This is followed 1 by a disc ussion of the averaging kernels and vertical resolution, and then estimates of the random uncertainties (precision) and systematic uncertainties are presented.

4.1 Characterization method

A general method for estimating the different con-ributions to the total uncertainty in retrieving an atmospheric constituent profile by any inversion technique is given by Rodgers [1990] (see also Marks and Rodgers, 1993). A brief outline of the method is presented below.

If the vector \mathbf{x} represents the true state of the atmosphere and the vector $\hat{\mathbf{x}}$ is the retrieved state then the total error in a retrieval is given, to first Order in small quantities, by

$$\hat{\mathbf{x}} - \mathbf{x} = [T(\bar{\mathbf{x}}, \hat{\mathbf{b}}, \hat{\mathbf{c}}) - \bar{\mathbf{x}}] - \mathbf{I} \mathbf{D}_y \mathbf{K}_b \epsilon_b + \mathbf{D}_y \epsilon_y - \mathbf{I} (\mathbf{A} - \mathbf{I})(\mathbf{x} - \bar{\mathbf{x}}), \tag{1}$$

where

 $\bar{\mathbf{x}}$ is the reference state of the atmosphere (for MLS $\bar{\mathbf{x}} = \mathbf{x}_a$, the a priori state),

 $\hat{\mathbf{b}}$ is an estimate of non-retrieved forward model parameters \mathbf{b} ,

ĉ is an estimate of the inverse model parameters c, e.g. a priori data,

the matrix \mathbf{K}_b , known as the model parameter influence function, is the sensitivity of the model radiances to the forward model parameter vector \mathbf{b} ,

 ϵ_b is the vector of uncertainties in b,

 ϵ_y is the measured radiance error vector.

The transfer function, T, relates the retrieved state $\hat{\mathbf{x}}$ to the unk n own true state \mathbf{x} by $\hat{\mathbf{x}} = T(\mathbf{x}, \mathbf{b}, \mathbf{c})$.

The contribution function, \mathbf{D}_y , is the sensitivity of the retrieval to the measurements \mathbf{y} .

The averaging kernel matrix, \mathbf{A} , is defined by

$$\mathbf{A} = \frac{\partial \hat{\mathbf{x}}}{\partial \mathbf{x}} = \mathbf{D}_y \mathbf{K}_x,$$

where \mathbf{K}_x is the influence function (also known as the weighting function) matrix of the atmospheric state, i.e. the sensitivity of the model radiances to a change in the state of the atmosphere.

Each row of the matrix A represents the vector of weights by whit.1] the true profile is multiplied to give the element of the retrieved profile corresponding to that row. For

an ideal observing system, A would be the identity matrix 1, but normally the rows of A will represent Peaked functions, with the width of the peak being a measure of the vertical resolution of the retrieval.

An expression for the total error covariance, S_T , of a retrieval is given, from equation (1), as

$$\mathbf{S}_T = \mathbf{S}_P + \mathbf{S}_M + \mathbf{S}_S$$

where

$$\mathbf{S}_{P} = \mathbf{D}_{y} \mathbf{K}_{b} \mathbf{S}_{b} \mathbf{K}_{b}^{T} \mathbf{D}_{y}^{T},$$

$$\mathbf{S}_{M} = \mathbf{D}_{y} \mathbf{S}_{\epsilon} \mathbf{D}_{y}^{T},$$

$$\mathbf{S}_{S} = (\mathbf{A} - \mathbf{I}) \mathbf{S}_{a} (\mathbf{A} - \mathbf{I})^{T}.$$

The matrix \mathbf{S}_P is the contribution to the retrieval error covariance of uncertainties in the model parameters, \mathbf{S}_b is the error covariance matrix for the forward model parameters. The matrix \mathbf{S}_M is the contribution of measurement noise to the retrieval error covariance, \mathbf{S}_{ϵ} is the measurement error covariance. The matrix \mathbf{S}_S is known as the 'smoothing' error. This can be regarded as the error that comes from the *a priori* error. The matrix \mathbf{S}_a represents the expected covariance of the departures of the true atmosphere from the *a priori* profile.

The method outlined in the above paragraphs has been applied to the Version 3 H₂O retrieval from band 5 of MLS for a typical mid-latitude case. Some important features of the calculations are mentioned and then a discussion of the results of this formal error characterization is given.

The influence functions (K matrices) were calculated for a typical mid-latitude atmosphere using the formulation of *Read et al.*, [paper in preparation], and were evaluated at

43 tangent pressures between z = -3 and z = +4 inclusively, with a separation in z of 1/6, where z is $-\log_{10}(p)$, p being pressure in hPa. These influence functions were then linearly interpolated onto a typical MLS scan pattern before the error calculations were performed. The retrieval levels chosen for H_2O were the same as those employed by the MLS Version 3 retrieval, i.e., 20 levels between z = -3 and +3.33 inclusively, with a separation of 1/3.

Typical a priori profile uncertainties used by the MLS retrieval were used to construct a purely diagonal covariance matrix, \mathbf{S}_a , which therefore assumes that no inter-level correlations are present. The measurement error covariance matrix, \mathbf{S}_{ϵ} , was constructed from typical MLS band 5 radiance errors under the assumption that no inter-channel correlations are present. The use of an opacity criterion (see section § 2) has also been built into the calculations. When estimating the extent of systematic errors in Π_2 O mixing ratio, for some systematic effects an equivalent error in radiance was estimated and a corresponding radiance error covariance matrix was constructed, i.e. essentially providing an estimate of $\mathbf{K}_b \mathbf{S}_b \mathbf{K}_b^T$. This error in radiance was then translated into an uncertainty in retrieved Π_2 O mixing ratio. For other systematic effects an estimate of the root-mean-square (rms) uncertainty in Π_2 O mixing ratio was given directly from sensitivity studies.

4.2 Averaging kernels and vertical resolution

We now discuss the MLS H_2O averaging k ernels. Figure 9 shows the resulting rows of the averaging kernel matrix for the -1 -120 retrieval at levels z = 2 to +3.33. The number printed at the peak of the functions represents the retrieval level, in $\log_{-10}(P)$ (pressure in hPa), associated with each averaging kernel.

In g eneral, b etween z = 1.67 and $+2(46 \cdot 0.01 \text{ hPa})$, the averaging kernels are well-

peaked functions with the peak coinciding with the level of the retrieval. In this region most of the information in the $\rm H_2O$ retrieval comes from the measurements and not from the a priori information. Below z=-1.67 (46 hPa), the averaging kernels are not so well peaked because there is little information in the measurements due to the band 5 channels becoming optically thick in this region. Above $z=\pm 2$ (0.01 hPa), the averaging kernels become wider and have smaller peaks due to the decreasing signal-to-noise ratio with altitude and the coarser steps of the FOV scan in this region.

As an estimate of the vertical resolution of the MLS Version 3 H₂O retrievals, the 'width' of each averaging kernel has been calculated using the Back us-Gilbert definition of spread [Backus and Gilbert, 1970] and is plotted in Figure 10. This gives the vertical resolution between z=1.33 and ± 0.67 (21.5 0.2 hPa) as ~ 5 km and from $z=\pm 1$ to ± 2.67 (0.1 O.(mill'a) as ~ 6 -10 km. The vertical resolution at z=-1.67 (46 hPa) is ~ 6 km.

From the information given by the averaging kernels alone, the useful vertical range for $Version 3 H_2 Or etrievals$ would be 46-0.01 hPa. However, other evidence, namely frequently-occurring high values at ~ 0.1 hPa which seem unrealistic, leads us to believe that the current useful vertical range is 46-0.2 hPa for Version 3 data.

4.3 Estimated Precision

We present three methods used to estimate the precision of the H₂O retrievals.

Method 1

This estimate of the precision is based on the formal analysis discussed above. The precision estimate is given by the root-sum-square of the random contributions to the retrieved

H₂O uncertainty which includes the measurement noise, the random errors in retrieved temperature and tangent pressure and uncertainties in other state vector parameters which affect the H₂O retrieval. Figure 11 shows a plot of the dominant random errors together with the root-sum-square (rss) of the random errors. In the lower stratosphere the random error is dominated by the uncertainty in the retrieved tangent pressure. However, the uncertainties in retrieved tangent pressure that are incorporated into the formal error analysis include some systematic effects [Fishbein et al., 1994]. Therefore, this method may lead to an overly pessimistic estimate of precision especially in the lower stratosphere. A comparison of this precision estimate with the precision estimates provided by methods 2 and 3 below is shown in Figure 12.

Method 2

This method involves calculating the variability of retrieved profiles near the orbit turning points (near 80°N or 80°S) in the summer hemisphere. It is at these latitudes that the densest sampling occurs and the summer hemisphere is chosen to minimise any effects from atmospheric variability. The line labelled (2) in Figure 12 shows the rms difference between pairs of profiles near the turning points. These profile pairs are less than 2 hours apart in time and are separated by less than 150 km. The time period used was 19th July 1992 to 8th August 1992 which gave 241 pairs of profiles near to 80°N.

Method 3

This method involves calculating the variability of retrieved profiles in the tropics where the atmospheric variability is usually small. The line labelled (3) in Figure 12 shows this estimate of precision. It is a result of calculating the standard deviation of retrieve d profiles in the latitude range 5°N-5°S for each one of 442 days and averaging the standard deviations over these days.

Comparing the precision estimates shown in Figure 12 arising from the three methods described above, we can see that methods 2 and 3 give very similar results. Method 1 gives a poorer estimated precision in the lower stratosphere and this may be related to the presence of systematic components in the retrieved tangent pressure uncertainty as mentioned above. An estimate of the precision for the useful vertical range of the H₂O retrievals is given in Section § 7. Note that the H₂O uncertainties given in the MI₂S Version 3 data files are somewhat greater than the estimates produced by the above methods. This is mainly because the MLS Version 3 uncertainties contain a contribution from the apriori error. This effect is strongest in the lows stratosphere. The MLS Version 3 errors also contain a systematic component which accounts for known differences between linear and nonlinear retrievals.

4.4 Estimated systematic uncertainties

In addition to random uncertainties, it is necessary to consider systematic uncertainties. Figure 13 shows the dominant systematic uncertainties along with the root-sum-square of all the systematic uncertainties considered. Below, we briefly discuss the various error sour ces which were considered in this analysis. Firstly we will discuss the sources of the dominant systematic uncertainties (see Figure 13).

tangent pressure: Since the retrieved mixing ratios are based 011 radiances at the retrieved tangent pressure then errors in tangent pressure can produce errors in mixing

ratio. Sensitivity tests were performed assuming a systematic error in tangent pressure of about 6 % [see Fishbein et al., 1994]. The main source of this systematic error is from possible errors in the O₂ spectroscopic data base. We can see from Figure 13 that these errors tend to dominate the systematic error between 2hPa and 0.2hPa.

temperature: Errors in temperature can lead to errors in mixing ratio. Sensitivity tests were performed taking biases in temperature to be 2 K for latitudes equatorward of 60 degrees and 5 K for latitudes poleward of 60 degrees. These biases are consistent with observed average differences between M 1,S and NM (; temperatures [see Fishbein et al., 1994]. Tangent pressure was retrieved while the temperature biases were imposed. The resulting changes in H₂O mixing ratio were e then analysed. [Hid-latitudes the systematic uncertainty in mixing ratio is generally about 1-2% for a 2 K systematic error in temperature.

retrieval numerics: this refers to the differences between the mixing ratio profiles used to create simulated noise-free radiances, and the subsequent retrieved profiles based on these radiances using the inversion algorithm. At ().1 hPa (outside the useful vertical range) this uncertainty is ~ 27 % which may account for the unrealistically high mixing ratios which can sometimes occur at this pressure level.

radiance scaling: three sources of scaling errors in calibrated radiances are radiometric calibration, sideband ratio errors and spectroscopic errors in linestrength. The first two error sources are discussed by Jarn of et al. [1994]. I Based on this reference, we use a systematic uncertainty of 0.6 % for the radiometric calibration of the 183 GHz radiometer which corresponds to about one-third of the worst-case error expected. This uncertainty is due mainly to uncertainties in the pre-launch characterisation of losses through the MLS antenna and switching mirror. A covariance matrix of radiance errors from this source was

constructed which assumes the errors are fully correlated across the band and with height. Errors in the sideband ratios can lead to possible errors in single sideband radiance of ~ 2 % for the 183 GHz H₂O band [see Jarnot et al., 1994]. These errors should be correlated in some way across the band but due to lack of knowledge of such correlations a covariance matrix of radiance errors was constructed which assumes no correlation is present. This gives a conservative estimate of the resulting uncertainty. For a systematic error in line strength we have assumed a value of 1 % based on Pickett et al. [1992] which is probably a conservative estimate of the line strength error. Again, a covariance matrix of radiance errors due to this source was constructed which assumes that the errors are fully correlated across the band and with height. The resulting uncertainties in 1 2O due to these three sources were combined by taking the root-sum-square uncertainty.

Field of view (FOV) direction: errors in the FOV direction are related to possible errors in misalignment of the 183 GHz radiometer FOV with respect to the 63 GHz FOV. Post launch calibration data from scans of the moon indicate a need for an alignment adjustment of the 183 GHz radiometer FOV from the pre-launch data (see Jarnot et al., 1994). The MLS Version 3 data used a misalignment value of 0.006 degrees which is somewhat less than the result of the studies based on moon-views of ().()11 degrees. We have assumed an uncertainty of 0.007 degrees in FOV direction (this is the uncertainty assumed in the MLS Version 3 data) and mapped this uncertainty into 11_2 O mixing ratio.

The following sources of systematic error were also considered but the resulting uncertainties in mixing ratio are generally not as significant as those which arise from the above-mentioned sources. The uncertainties in mixing ratio from the sources below are not plotted but have been included in the estimate of the root-sum-square systematic uncer-

tainty shown in Figure 13.

spectroscopy: errors in spectroscopic parameters can give rise to errors in retrieved mixing ratio. Line positions are known extremely accurately at microwave wavelengths and therefore do not represent a significant error source. Uncertainties in line strength have been included in the radiance scaling uncertainty mentioned above. Possible errors in linewidth were treated by assuming an uncertainty of 1.8% in the broadening function and an uncertainty of 4% in the temperature exponent. These uncertainties were estimated by combining information from Bauer et al., [1989] and Goyette and De Lucia, [1990]. We also include a related uncertainty from imperfect knowledge of the Doppler shift of the emitted radiation, produced by line of sight velocity effects. Atmospheric windalong the line of sight will be the dominant source of error since both the spacecraft and earth velocity components are reasonably well known. An uncertainty of 70 m/s in line of sight velocity was assumed. The root-sum-square uncertainty in H₂O mixing ratio due to these three error sources is generally less than 2%, although an uncertainty of 4% is produced at 0.46 hPa which is due to the uncertainty in line of sight velocity.

dry air continuum: the dry air continuum is a semi-empirical contribution which is derived from radiance data from the 205 GHz radiometer [see Read et al., paper in preparation]. Possible errors produced by imperfect knowledge of the dry air continuum are estimated by assuming that no dry air continuum is present in the forward mode], and comparing the subsequent retrieved 11,0 mixing ratios with a standard retrieval. This is a 'worst case' scenario. The rms error in mixing ratio is estimated by dividing the worst case error by 3. This error source is only significant in the lower stratosphere where an uncertainty of ~ 1.5% occurs at 46 hPa and an uncertainty somewhat less than % occurs at 22 hPa.

FOV shape and position: FOV shape and position errors of the 183 GHz radiometer have been transformed into errors in radiance [Jarnot, personal communication, 1994]. A 1σ error of 0.5 K is assumed and a covariance matrix of radiance error due to this source was constructed assuming these errors to be fully correlated across the band. The resulting uncertainty in H₂O mixing ratio is generally less than 1 %.

filter shape: each frequency channel across the $\rm H_2O$ band of the 183 GHz radiometer has an associated filter shape and position. Filter position errors are negligible but errors in filter shape could give rise to worst case errors in calibrated radiance of $\sim 0.5\%$ [Jarnot, personal communication, 1994]. A covariance matrix of radiance error due to this source was constructed with no correlations between channels. The resulting uncertainty in 11_20 mixing ratio is negligible compared to the other systematic uncertainties mentioned above.

Finally, we give an estimate of the total uncertainty in MLS 1120 derived from the estimated uncertainties, both random and systematic, mentioned above. We also include the smoothing error [Marks and Rodgers, 1993] which represents the contribution of the a priori errors to the retrieved uncertainty. Figure 14 shows the estimated precision (from method 3 above), the root-sum-square (rss) systematic uncertainty and the smoothing error along with the root-sum-square of these three uncertainties. In section § 7 we give a summary table of the estimated precision (from method 3 above) and accuracy (rss error in Figure 14) for the useful vertical range of MLS Version 31120 data.

5. Comparison of MLS and correlative measurements

We now compare MLS Π_2O data with measurements from four other observing systems. Two of these, a frost-point hygrometer and an infrared spectrometer are balloon-mounted. The other two are a ground-based microwave spectrometer and a satellite-borne instrument which measures infrared absorption during solar occultations.

5.1 Frost point hygrometer data.

This instrument has an altitude range from the ground to ~28 km with a vertical resolution of 250 m. The accuracy of these measurements is 10 %; their precision is 1 0 % in the stratosphere [11?/]) s, person (11 communications, 1992]. The measurement sites which have have been used in this MLS-correlative comparison are: Boulder (40.0°N, 105.00\V)," Hilo, Hawaii (19.7°N, 204.9°E), and Lauder, New Zealand (45.00s, 109.4°E). Data were also taken during the Central Equatorial Pacific Experiment (CEPEX) at approximately (2.0°N, 157.5°W).

We have used the 12 balloon profiles distributed over these sites, for which there was coincident MLS water vapour data. 1"igure 15 shows a typical profile, taken in this case at IIilo. Some of the closest MLS profiles are shown for comparison. The two data sets overlap over a restricted height range; the balloon data and the MLS data can be usefully compared at the 22 and 46 hPa levels. We tll(>10 fore calculated the differences between each balloon profile and the nearest MLS profile at these levels. At 46 hPa, the mean difference (MLS-balloon), taken over these 12 comparisons, is 0.2 ppmv, while the root mean square difference is 0.5 ppmv. At 22 hPa, the mean difference is 0.1 ppmv and the rms difference is 0.4 ppmv, the average being taken over the 6 balloon flights which reached a sufficient altitude for a comparison to be made at this level. We conclude that the systematic bias between the two data sets is smaller than 0.2 ppmv and that the random differences are within the quoted uncertainties. We note that none of the profiles used are at a latitude

5.2 Ground-based microwave data.

This instrument is a ground-based water vapour milli meter wave spectrometer. All measurements used in this comparison have a vertical range between 30 and 80 km. The total absolute error of these meas u rements is ~ 10 % over the height range 40-70 km [Nedoluha et al., 1995]. This technique has a vertical resolution of ~15 km. This is considerably coarser than the resolution of MLS, so for a better comparison it would be desirable to smooth the MLS data using the averaging kernels of the ground-based instrument. We have not done this so it should be borne in mind that MLS may detect features in the atmosphere which the ground-based instrument cannot resolve. The measurement site is Table Mountain Observatory (TMO), situated at 34.4°N, 243.0°E, the data is a daily average and is provided with a pressure grid, the conversion from height to pressure having been performed using temperature and P ressure fields from the National Meteorological Center (NMC) and the Middle Atmosphere Program (MAP) model [Hedin, 1991].

h41,S Version 3 data are compared with Version 2 of the ground-based data in Figure 16, where we plot both the mean difference (MLS – ground-based) and the rms difference. Data used in the comparison are from the period of 23rd January 1992 to 13th October 1992; this period provided a total of 186 days on whit.] 1 both MLS and ground-based measurements were available. The rms difference is not much greater than the mean difference, suggesting that much of the difference between the two data sets is systematic. The ground-based data is less accurate at lower altitudes; some of the difference at 2.2hPa and perhaps 1.0hPa may be attributed to this. The MLS Version 3 values at 0.46 and 0.22hPa are probably too

large by about 1 ppmv. The MLS Version 3 value at ().1 III)a is often as great as 10 ppmv. This is thought to be an artifact of the retrieval which we hope to remove in subsequent versions of the processing software. It is for this reason that we recommend that data from 0.1 hPa and above should not be used for scientific purposes.

5.3 FIRS-2 data.

This instrument is an illfra-reel emission Fourier transform spectrometer carried by a balloon [Johnson et al. 1994]. Its vertical range is approximately 100-3 hPa, with a sampling interval of approximately 4 km, conveniently filling in the gap between the frost-point hygrometer and ground-based microwave data sets. It made three flights during the period when the 183 GHz radiometer of MLS was operational, at times and places chosen to coincide with UARS lillill)-view'i lightc:as~l lcl~lrllts. Figure 17 shows a FIRS-2 profile and an MLS profile. As with the frost-point hygrometer data, the profiles agree well in the lower stratosphere. Furthermore, the MLS profile becomes greater than the FIRS-2 profile as height increases, suggesting that the difference between the ground-based microwave data and MLS data is largely because MLS data are too high, rather than because the ground-based values are too low. These features are repeated in the other two 1"11{S-2 flights.

The MLS Version 3 software cannot retrieve water vapour at 1 ()() hPa. The values it produces are almost entirely clim atological, but it is worth remarking that they are always too high when compared with correlative data. It will be possible, by using a nonlinear retrieval, to measure water vapour at this level; the comparison with correlative data suggests that a revised climatology is desirable before this is attempted. It is planned that future versions of the software will use a climatology which incorporates the SAGE II

5.4 HalogenOccultationExperiment (HALOE) data

In this section we present a comparison of MLS Version 3 H₂O data with Version 17 H₂O data from the HALOE instrument which is also onboard UARS. The Halogen Occultation Experiment (HALOE) is a **limb** sounding instrument **which measures** atmospheric absorption of solar infrared radiation during sunrise and sunset events. The characteristics of the UARS orbit and the solar occultation combine to p roduce a coverage pattern giving 15 sunrise profiles at one particular latitude and 15 sunset profiles at a different latitude 011 each day! These profiles are spaced $\sim 24^{\circ}$ apart in longitude with the latitude coverage changing throughout the year [Russell at al., 1993]. HALOE is capable in clear air of measuring profiles from ~ 0.01 hPa to cloud top, i.e. the tropopause or lower. The overall accuracy of the HALOE Version 17 11₂0 profiles is estimated to be 20-25% in the lower stratosphere, 10 15% in the upper stratosphere and 15-20% in the lower mesosphere. The vertical resolution of the HALOE profiles is $\sim 2 \, \text{km}$.

The differing coverage patterns of the MLS and HALOE instruments limit the latitudinal range and temporal extent of the comparison. During periods when the coverage patterns overlap, MLS data is used to build a representation of the way in which HALOE samples the atmosphere. These periods are normally around 20 days in duration. For each day within one of these periods, the average latitude of the HALOE profiles was calculated. Then, for the ascending and descending orbit modes of MLS, the profiles enveloping this average HALOE latitude were found. The corresponding MI, S profile, for each orbit, at the average HALOE latitude was then obtained by linear interpolation. The zonal mean difference

between the MLS profiles and the HALOE profiles (MLS-HALOE) was then calculated for acluday of the comparison.

Figure 18 shows a contour plot of this zonal mean difference for the period 21st January 993 to 8th February 1993. The latitudinal coverage for this comparison period is from 30°N at the beginning of the period to 50°S at the end of the period. The zonal mean difference is expressed in units of ppmv. The comparison in Figure 18 uses MLS data from ascending orbit tracks only, however, similar features are produced when using data from descending orbit tracks. The results of this particular comparison are typical of those from other periods which have been studied.

In the lower stratosphere MLS and HALOE H₂O values differ by less than 0.5 ppmv (10%) with MLS values tending to be larger than HALOE values. At 46 hPa the MLS values can be slightly less than those of HALOE. These differences are comparable with the H₂O error estimate produced by the MLS retrieval algorithms for this region of the atmosphere. In the upper stratosphere and lower mesosphere MLS H₂C values are consistently higher than the HALOE values by 1.0-1.5 ppmv (1020 %). These differences tend to be greater than the MLS error estimate and are also consistent with comparisons with other correlative measurements presented earlier in this section. At (), [])]) a the MLS H₂O values can be as much as 3 ppmv (30%) larger than the HALOE values. At this pressure level the MLS Version 3 []₂O values are considered to be unphysically large (see section § 6).

6. Tepics for Future Work

While the Version 3 water vapour is a useful quantity there are some problems associated

•

stratosphere and tends, therefore, to bring the MLS water vapour into better agreement linewidth—nan was assumed in the Version 3 software. Tests show that using the corrected that the oxygen lines used to retrieve temperature and pressure have a slightly smaller with t and improvements which can be made. Recent research [Liebe et al., 1992] has shown smaller discrepancies between measured and calculated radiances. with the correlative measurements. Also, using the new oxygen linewidths gives rise to is less than 0.2 ppmv in the lower stratosphere, and is typically 0.3-0.5 ppmv in the upper linewidths gives somewhat lower values for water vapour in the stratosphere. The decrease

present would make the retrieval better rather than worse. This cannot be implemented 3 is ather stricter than necessary and that using a few more radiances than are used at required to make full use of them. Tests have suggested that the criterion used in Version are related nonlinearly to the water vapour content so a nonlinear retrieval process would be radiances which come from ray paths which are judged to be optically thick. These radiances at polar latitudes. The information is lost because the Version 3 software does not use immediately because it causes other problems, particularly with the baseline. A serious problem is the loss of information which occurs at 46 and 22 hPa in the winter

level. at 0.1 hPa. The center channel, channel 8, becomes optically thick and is not used at this level while channels 7 and 9 only have sufficient signal to retrieve water vapour below this The same tests suggest that a similar problem is at least partly responsible for the notch

retrieval. Initial tests show that it is possible to retrieve water vapour at 100 hPa by this version. However, to extract full information from the measurements will require a non-linear With these changes, a future linear retrieval should be an improvement on the current technique. It is also possible [Read et al. 1994] to retrieve upper tropospheric water vapour rom MLS band 3 (at 206 GHz), normally used for stratospheric chlorine monoxide. We blan to include this information along with that from the 183 GHz radiometer into a single etrieval process, producing a measurement of water vapour from the upper troposphere to the mesosphere.

In addition to these major changes, there are some minor artefacts in the data which we plan to climinate. There are occasional profiles for which the retrieval has clearly failed, but which are not flagged as being bad. One known cause occurs during the generation of calibrated radiances (Level 1 data) and will be eliminated in future versions of the software. Another artefact occurs in the data at 22111'a which show a small systematic dependence plus the UARS yaw cycle. This effect is not fully understood at present, but is clearly an artefact which needs to be removed. At 1 important improvement will be the use of a revised climatology; the current version 'is supplying unsuitable a priori values at 100 hPa. Finally, tracer transport studies [Manneyetal., 1994] suggest that MLS water vapour in the upper stratosphere dots not behave like a passive tracer. We aim to establish whether this is an artefact of the retrim'al or the tracer transport code, or whether it is a real physical effect.

7. Estimated Accuracy and Precision of MLS Version 3 Data

MLSVersion 3 H₂Oretrievals give reasonable values in the stratosphere, but consistently overestimate other correlative measurements. The current range of useful sensitivity (as measured by the data quality see section § 4) is between 46 hPa and ().() III'a, although lower mesospheric retrievals appear suspect at present due to a '1 lotch' are und~ 0. 1 hPa (see section § 6). Retrievals at 46 hPa in the polar winter can have poor data quality (see

٠.

section § 2). Therefore, the recommended pressure range for scientific studies using MLS 1120 is from 22 hPa to ().2111'a for all latitudes, and from 46111'a to 0.2 hPa at the tropics and mid-latitudes.

Comparison with other 11_20 measurements suggests that MLS 11_20 values are too high by $\sim 5\%$ at $46\,\mathrm{hPa}$ and at $22\,\mathrm{hPa}$ and by $15\,20\%$ in the range $1\,\mathrm{hPa}$ to $0.22\,\mathrm{hPa}$.

Acknowledgm [71 1.5.] We thank many colleagues, at Edinburgh University, Heriot-Watt University and the Rutherford Appleton Laboratory in the United Kingdom and at the Jet Propulsion Laboratory in the USA, who have contributed to the MLS project. We are indebted to various persons from the UARS Project and elsewhere for the compilation of data and model values which make up the "UARS Climatology File", which is used as a priori information in the MLS retrieval process; in particular, we acknowledge the efforts of R. Scals and P. Connell. We also thank M. Allen for the default model profiles used as part of this procedure. Early simulations of MLS retrievals also benefited from the availability

of 3-D model results, made possible by W.L. Grose, G. Lingenfelser, and others at the NASA Langley Research Centre. We thank the groups at NOAA Climate Monitoring and Diagnostics Laboratory, the Naval Research Laboratory, Harvard-Smithsonian Centre for Astrophysics and NASA Langley Research Centre for kindly providing correlative data sets. The work in the UK was funded by SERC and NERC, and in the USA by NASA.

References

- Backus, G.E., and J.F. Gilbert, Uniqueness in the inversion of inaccurate gross Earth data,

 Philos. Trans. R. Soc. London, Ser. A266, 123-192, 197 (1.
- Barath, F.'J., M.C.Chavez, R.E.Cofield, 1). A. 11'lower, M.A.Frerking, M.B.Gram, W.M.
 Harris, J.R. Holden, R.F. Jarnot, W.G. Kloezeman, G.J. Klose, G.K. Lau, M.S. Loo,
 B.J. Maddison, 1 { . . 1 . Mattauch, R.P. McKinney, G.E. Peckham, H. M. Pickett, G.
 Siebes, F.S. Soltis, R. A. Suttie, J. A. Tarsala, J.W. Waters, and W.J. Wilson, The Upper Atmosphere Research Satellite Microwave Limb Sounder instrument J. Geophys.
 Res. 98, 1)6, 10,751-10,762, 1993.
- Bauer, A., M. Godon, h 4. Kheddar, and J.M. Hartmann, Temperature and perturber dependences of water vapor line-broadening. Experiments at 183 GHz; calculations below 1000" GHz, J. Quant. Spectrosc. Radiat. Transfer 41, No. 1, 49-54, 1989.
- Bevilacqua, R. M., W.,]. Wilson, W.B. Ricketts, P.R. Schwartz, and R. J. Howard, Possible seasonal variability of mesospheric water vapor, Geophys. Res. Lett. 12, 397-- 400," 1985.
- Bevilacqua, R.M., W.]. Wilson, and 1'.1{. Schwartz, Measurements of mesospheric water vapor in 1984 and 1985: results and implications for middle atmospheric transport, ,1.

 Geophys. Res. 92, 106, 6679-6690, 1987.

- Fishbein, E.F., W.G. Read, L. Froidevaux, and J.W. Waters, Validation of temperature and pressure measurements by the Upper Atmosph ere Research Sat ellite Microwave Limb Sounder, J. Geophys. Res., submitted, 1994.
- Froidevaux, 1,.., W. G. Read, T. A. Lungu, R.E. Cofield, E. F. Fishbein, 1). A. Plower, R. F. Jarnot, B.P. Ridenoure, Z. Shippony, J.W. Waters, J.J. Margitan, 1.S. McDermid, R. A. Stachnik, G.E. Peckham, G. Braathen, 'J'. Deshler, J. Fishman, D. J. Hofmann, and S..1. Oltmans, Validation of UARSMLS ozone measurements, J. Geophys. Res., submitted, 1994.
- Goyette, T.M. and F.C. De Lucia, The pressure broadening of the 3_{1,3}- 2_{2,0} transition of water between 80 K and 600"1<, J. Mol. Spectroscopy 143, No. 2, 346--358, 1990.
- Hedin, A.E., Extension of the MSIS thermosphere model into the middle and lower atmosphere, J. Geophys. Res. 96, A2, 1159-1172, 1991.
- Jarnot, R.F., R.E. Cofield, G.E. Peckham, and J.W. Waters, Calibration of UARS MLS, J. Geophys. lies., submitted, 1994.
- Johnson, 1)..1., K.W. Jucks, W.A. Traub and K.V. Chance, The Smithsonian stratospheric far-infrared spectrometer and data reduction system, J.G. R., in press, (1994).
- Liebe, 11..1., P.W. Rosenkranz, and G.A. Hufford, Atmospheric 60 GHz oxygen spectrum: new laboratory mea surements and line parameters, J. Quant. Spectrosc. Radiat. Transfer 48, 629-643, 1992.
- Manney, G.L., W.A. Lahoz, R.S. Harwood, R.W. Zurek, J. B. Kumer, J.L. Mergenthaler,
 A.E. Roche, A. () 'Neill, R. Swinbank, J.W. Waters, Lagrangian transport calculations:
 using UARS data. Part 1: Passive tracers, J. Atmos. Sci., submitted, 1994.

- MA I', J.J.Barnett, and M. Corney, llandbook for Middle Atmosphere Program (MA))>
 SCOSTEP Secretariat, University of Illinois, Urbana, USA, 1989.
- Marks, C.J., and C.D. Rodgers, A retrieval method for atmospheric composition from limb emission measurements, J. Geophys. Res. 98, D8, 14, 939-14, 953, 1993.
- Nedoluh a, G.E., R. M. Bevilacqua, R. M. Gomez, 1).1, Thacker, W.B. Waltman, and T. A. Pauls, Ground-based measurements of water vapor in the middle atmosphere, J. Geophys. Res. 100, 1)2, 1995.
- Pickett, H. M., R.L. Poynter, and E.A. Cohen, Submillimeter, millimeter and microwave spectral line catalog, Technical report 8023, Revision 3, Jet Propulsion Laboratory, 1992.
- Read, W.G., J.W. Waters, L. Froidevaux, 1). A. Flower, R.F. Jarnot, D.L. Hartmann, 14. S. Harwood, and R.B. Rood, Upper tropospheric water vapor from UARS MLS, Bull. A mer. Met. Soc., submitted, 1994.
- Reber, C. A., The Upper Atmosphere Research Satellite Trans. Am. Geophys. Un. 7 1, No. 51, 1,867-1,868, 1,873-1,874,1,878,1990.
- Remsberg, E.E., J.M.Russell 111, and C.-Y. Wu, An interim reference model for the variability of the middle atmosphere water vapor distribution, Adv.SpaceRes.10, 51 64, 1990.
- Rind, 1)., E.-W. Chiou, W. Chu, S. Oltmans, J. Lerner, J. Larsen, M. 1'. McCormick, L.McMaster, ovm-view of the Stratospheric Aerosol and Gas Experiment 11 Water Vapour Observations: Method, Validations and 1 Data Characteristics, J. Geophys. Res. 98, 1)3, 4835-4856, 1993.

- Rodgers, (3.1)., Retrieval of atmospheric temperature and composition from remote measurements of thermal radiation, Rev Geophys. and Space Phys. 14, 609-624, 1976.
- Rodgers, C.D., Characterization and error analysis of profiles retrieved from remote sounding measurements, J. Geophys. Res. 95, D5, 5587--5595, 1990.
- Russell 111, J. M., J.C. Gille, E.E. Remsberg, 1,1, Gordley, 1'.1, Bailey, 11. Fischer, A. Gird, S. 1{. 1 Drayson, W.F.J. Evans, and J.E. Harries, Validation of water vapor results measured by the Limb Infrared Monitor of the Stratosphere (LIMS) experiment on NIMBUS 7, J. Geophys. Res. 89, D4, 5115 5124, 1984.
- Russell 111, J.M., L.L. Gordley, J.]]. Park, S.R. Drayson, W.D. Hesketh, R.J. Cicerone, A.F. Tuck, J.E. Frederick, J.E. Harries, and P.J. Crutzen, The Halogen occultation Experiment, J. Geophys. Res. 98, D6, 10,777-10,797, 1993.
- Tsou, J- J., J..), Olivero, and C.L. Croskey, Study of variability of mesospheric 11₂0 during spring 1 984 by gmuI]cl-based microwave radiometric observations, J. Geophys. lies. 93, 1 05, 5255-5266, 1988.
- Waters, J.W., Absorption and emission by atmospheric gases, in *Methods of Experimental Physics*, 12B, (I. Meeks, d.), 142-176, Academic Press, New York, 1976.
- Waters, J.W., Microwave Limb Sounding, in Atmospheric Remote Sensing by Microwave Radiometry, (M.A. Janssen, ed.), ch. 8, John Wiley & Sons, New York, 1993.
- Waters, J. W., W. G. Read, L. Froidevaux, T. Lungu, V.S. Perun, R.A. Stachnik, R.F. Jarnot, R.E. Cofield, E.F. Fishbein, D. A. Flower, J.R. Burke, J.C. Hardy, L.L. Nakamura, B.P. Ridenoure, Z. Shippony, R.P. Thurstans, 1.. M. Avallone, D. W. Toohey, R.L. deZafra, and 1).'1'. Shindell, Validation of UARS MLS CIO measurements, J. Geophys. Res., submitted, 1994.

Figure Captions

Fig. 1: Calculated limb emission in the spectral region 182-187 GHz which includes both spectral sidebands of MHS band 5 (vertical dashed lines) and band (i (vertical dotted lines). The position of the 183 GHz radiometer local oscillator (1,()) at 184.78 GHz is indicated. Spectra for tangent pressures of 46 hPa and 4.(; hPa are plotted.

Fig. 2: MLS band 5 (183 GHz H₂O) limb radiance profiles for channels 1-8 for a tropical profile (4.25°N, 334.99°E) on 10th January 1992.

Fig. 3: MLS band 5 (183 GHz 11₂0) radiance spectra for a tropical profile (4.25 °N, 334 .99 °E) 0.11 1 0th January 1992 at three tan gent pressures: 0.11 hPa (top panel), 3.7 hPa (middle panel) and 50111'a (bottom panel).

Fig. 4: radiant.cs from channels 1 to 8 for a MLS scan at latitude 56.05°N, longitude 255.13°E on 1 0th January 1992. Also shown, by the thick line, is the MLS temperature profile, scaled by the 0.58 sideband ratio. Note that the baseline is about 2 1<; the radiances tend to this value as height increases.

Fig. 5: MLS band 5 radiance residual profiles for channels 1-15 for 10th January 1992 at $(4.25^{\circ}\text{N}, 334.9~9^{\circ}\text{E})$. The horizontal bars represent the 1σ measurement noise.

Fig. 6: MLS band 5 average radiance residual spectra for 10th January 1992 within latitude band 10°N-10°S. The pressure range is displayed above each panel. Vertical bars represent the standard error on the mean measured radiance. The number of limb views included in the calculation of the average radiance residual ranges from around 200 in the pressure

range 0.032-0.01 hPa to around 800 in the pressure range 100-31.6 hPa

range 0.032 0.01 hPa to around 800 in the pressure range 100 31.6 hPa the standard error on the mean measured radiance. The number of limb views included in the calculation of the average radiance residual ranges from around 200 in the pressure band 60°N-80°N. The pressure range is displayed above each panel. Vertical bars represent) and 5 average radiance residual spectra for 10th January 1992 within latitude

on the true distribution, units are ppmv. (c) zonal mean difference (retrieval truth) H_2O , units are ppmv. (d) rms difference between etrieval and truth, units are ppmv 17th September 992) (b) zonal mean of retrieved H₂C using simulated radiances based tests of retrieval closure, units are ppmv (field taken from MLS Version 3 $\rm H_2O$ retrieval for zonal mean of smoothed ₂O field used to represent the true distribution i

Fig. 9: Averaging kernels for M S Version 3 H₂O retrievals.

Fig. 10: Vertical resolution of M.S Version 3 H₂O retrievals

ppmv Line (1) is an estimate of precision given by method Estimated random errors associated with the retrieval of MLS H₂O. The units are o section § 4.

hemisphere, method 3: variability of retrieved profiles in the tropics. The units are ppmv. method 2: variability of retrieved profiles near to the orbit turning points i the summer Fig. 12: Precision estimates for MLS Version 3 II₂O. Method 1: from formal error analysis,

13: Estimated systematic uncertainties associated with the retrieval of MLS $\rm H_2O$

Fig. 14: Estimated uncertainties associated with the retrieval of MLS H₂O. rss error: root-sum-square of precision, systematic error and smoothing error, precision (3): estimate of precision using method 3 (see text), rss systematic error: root-sum-square of estimated systematic errors, smoothing error: contribution of the *a priori* errors.

Fig. 15: A typical water vapour profile measured by a balloon mounted frost point hygrometer (solid line). The balloon was launched from a site in Hawaii at latitude 19.4°N,
longitude 155°W, on 24 March 1991. Several MLS profiles for nearby locations are shown
by dashed and dot-dash lines, their error bars are shown by dotted lines. The balloon profile
is within the MLS errors at 46 and 22 hPa.

Fig. 16: Comparison of MLS Version 3 water vapour with the Version 2 data from the ground-based microwave instrument. 1 Data are from the period of 23rd January 1992 to 13th October 1992; a total of 186 days for which both MLS and ground-based measurements were available. The 1eft hand plot shows mean profiles; the solid line is MLS data, the dashed line ground-based. The right hand plot shows the mean difference, MLS - ground-based (solid) and the rms difference (dashed).

Fig. 17: Water vapour profiles measured by MLS (solid line) compared with FIRS 11 (squares) on 29 September 1992. The MLS profile is at latitude 37.5 °N, longitude 103.2 °W, the FIRS II profile is at latitude 36.9 °N, longitude 100.4 °W.

Fig. 18: Zonal mean difference (MLS -- HALOE) between MLS Version 3 H₂O and HALOE Version 17 H₂O for the period 21st January 1993 to 8th February 1993. The numbers along the top of the plot are the UARS day numbers for which each zonal mean difference profile

RG6 2A W.A. Jahoz, CGA Department o Meteorology, Reading University, England, UK

Edinburgh University, Scotland, K 3H9 3JZ R.S. Harwood, W.A. Jahoz, H.C. Pumphrey, M.R. Suttie, Department of Meteorology,

Scotland, UK EH14 4AS C.L.Lau, G.F. Peckham, R.A. Suttie, Department of Physics, Heriot-Watt Jniversity,


Laboratory, California Institute o Technology, 'asadena, CA, USA 91109 Froidevaux T.A. Lungu, W.G. Read, Z. Shippony, J.W. Waters, Jet Propulsion


s: 3 Nedoluha, Naval Research Laboratory, Code—220 Washington, Del JSA 20375

USA 80303 S. Oltmans, NOAA Climate Monitoring and Diagnost cs Laboratory, Boulder, CO,


J.M {ussel NASA langley lesearch Centre, Hampton VA, USA 23665


W.A Traus, arvard-Smithsonian Centre for Astrophysics, Cambridge, MA, USA 02138






Figz







F195







Fig 5










Fig 9




Fig 10




Fig 11




Fig 12









Fig 13











Fy 18

UARS Standard	1'1'('ss111'('	Single Profile Precision 1)		$\Lambda_{ m ccura} { m cy} (2)$	
Levels	(hPa)	(ppmv)	(percent)	(ppmv) (1)('1 '('('11{)	
22	0.22	0.45	(0.9	13
20	0.46	0.33	5	0.7	11
18	1	0.25	1	().7	10
16	2.2	0.20	3	0.6	9
14	4.6	0.17	3	0.5	8
12	10	0.13	3	(). (-)	9
10	22	0.14	4	(). s	19
8	46	0.20	5	1.2	25

Table 1: $MLSH_2O$ data summary. (1) The estimated precisions are based on the observed variability of retrievals in the tropics (see Method 3 of Estimated Precision in section § 4). (2) The estimated accuracies are based on the (1'1'01" analysis presented in s((-tie]] § 4.